

Dual Concentric Mica Tape Machine

Encintadora concéntrica doble para Mica



EN

- High speed dual concentric mica taping head.
- Designed for mica taping on fire resistant cables.
- Tape tension control is done through hysteresis brake.
- Taping head and pulling capstan are driven independently by AC servo motor.
- HMI+PLC control system for pre-setting taping pitch, tape tension compensation and speed synchronization.

ES

- Encintadora concéntrica doble de alta velocidad .
- Diseñada para encintado con mica de cables anti fuego.
- Control de tensión de la cinta mediante freno de histéresis.
- Accionamiento independiente del cabestrante de tiro y de la encintadora mediante servo motor AC.
- Sistema de control HMI+PLC para la selección del paso, compensación de tensión y sincronizado de velocidad.



Model / Modelo

NM-40H

D:	400
----	-----

Pad size / Dimensión rollo [mm]:

d:	76
----	----

W:	30
----	----

D:	300
----	-----

Bobbin size / Dimensión bobina [mm]

d:	76
----	----

W:	210
----	-----

Cable Ø / Ø Cable [mm]

1-10

Taping speed (Pad/Bobbin) / Velocidad (Rollo/Bobina) [rpm]:

2000/1500

Pad length / Almacenamiento [mm]

1000

Motor power / Potencia motor [kW]

3.7 AC